

SOLDERING TABLE

PK-IAT-L



Energy and airflow-optimised extraction table with supply air curtain and Coanda effect baffle plate suction.



Standard equipment

- Height-adjustable feet (mech.) + 70 mm
- Earthing connection, chassis connection
- 5 mm steel work surface
- LED task light with adjustable angle of illumination, IP 65, 230 V
- Connection cable with commando plug, length 5 m (approx.)
- Stainless steel side curtain rails
- Switched socket outlet



Special equipment (at extra cost)

- Stepless height adjustment with electric lift cylinder
- Air curtain with incl. ON/OFF switch
- Extract fans and filtering systems
- Pre-assembled system pipework
- Special colours, special paint finishes (RAL)
- Clear PVC strip antistatic curtains
- Welding protective curtains S9 dark green
- Fixed and folding steel side walls
- Rotary tables and vices
- ATEX zone 1/21 LED light

SOLDERING TABLE

TYPE	PK-IAT-L 1000	PK-IAT-L 1400	PK-IAT-L 2000
Art. No.	A40021	A40022	A40023
Work surface width x depth	1000 x 900 mm	1400 x 900 mm	2000 x 900 mm
Working height	875 mm	875 mm	875 mm
Table interior height	1165 - 1275 mm	1165 - 1275 mm	1165 - 1275 mm
Overall width	1195 mm	1595 mm	2195 mm
Table height	2388 mm	2388 mm	2388 mm
Overall depth	1148 mm	1148 mm	1148 mm
Typical extraction rate and ACPH	800 m ³ /h / 15 x	1200 m ³ /h / 15 x	1700 m ³ /h / 15 x
Supply air	Approx. 250 m ³ /h	Approx. 250 m ³ /h	Approx. 250 m ³ /h
Exhaust connection	DN 200	DN 200	DN 250
Weight	200 kg	245 kg	325 kg