

CLEANING TABLE WITH COLLECTING TRAY, COLLECTING BASIN AND STAINLESS STEEL BALL VALVE

PK-IAT-R



Energy and airflow-optimised extraction table with supply air curtain and Coanda effect baffle plate suction.

CLEANING TABLE WITH COLLECTING TRAY, COLLECTING BASIN AND STAINLESS STEEL BALL VALVE

TYPE	PK-IAT-R 1000	PK-IAT-R 1400	PK-IAT-R 2000
Art. No.	A40060	A40061	A40062
Work surface width x depth	1000 x 900 mm	1400 x 900 mm	2000 x 900 mm
Working height	875 mm	875 mm	875 mm
Table interior height	1165 - 1275 mm	1165 - 1275 mm	1165 - 1275 mm
Overall width	1195 mm	1595 mm	2195 mm
Table height	2388 mm	2388 mm	2388 mm
Overall depth	1148 mm	1148 mm	1148 mm
Typical extraction rate and ACPH	1000 m ³ /h / 18 x	1400 m ³ /h / 18 x	2000 m ³ /h / 18 x
Supply air	Approx. 250 m ³ /h	Approx. 250 m ³ /h	Approx. 250 m ³ /h
Exhaust connection	DN 200	DN 200	DN 250
Weight	200 kg	230 kg	330 kg



Standard equipment

- Height-adjustable feet (mech.) + 70 mm
- Earth connection
- LED task light with adjustable angle of illumination, IP 65, 230 V with polycarbonate impact and dirt protection
- Connection cable with commando plug, length 5 m (approx.)
- Stainless steel side curtain rails
- 2 x V2A perforated plate elements, 1 x enclosed
- Stainless steel drainage and collection tray with ball valve
- Supply air unit with aerodynamically optimised baffle plate suction



Special equipment (at extra cost)

- 1 set of clear PVC strip antistatic side curtains
- Supply air fan including the ventilation connections
- ON/OFF switch
- Extract fan and exhaust systems
- Customer choice of RAL colours
- Spacers to adjust height of work surface by 80 mm
- Side walls in steel or stainless steel sheet
- Extract air pipework
- ATEX zone 1/21 LED light